

MONITOR

YIP-A5604MHB



YIP-P4004M-L8H

High Brightness

LED Type

5.6 インチ



High Brightness

YIP-A5604HB

6.4 インチ



YIP-P6401
YIP-P6404

7.0 インチ



YIP-A7001

仕様 Specification

Model	YIP-P4004M-L8H	YIP-A5604MHB
Display Method	Color TFT LCD	Color TFT LCD
Back Light	LED	CCFL
Resolution	960 (H) x 234 (V) dot	960 (H) x 234 (V) dot
Active Area (mm)	81.12 (H) x 61.776 (V)	113.3 (H) x 84.7 (V)
Dot Pitch (mm)	0.0845 (H) x 0.264 (V)	0.118 (H) x 0.362 (V)
Pixel Configuration	R.G.B Stripe	R.G.B Stripe
View Angle	Top : 10° Bottom : 30° Right : 45° Left : 45°	Top : 30° Bottom : 50° Right : 50° Left : 50°
Dimension (mm)	134.0 (W) x 105.0 (H) x 22.0 (D)	156.0 (W) x 122.0 (H) x 31.0 (D)
Input Voltage	DC12V± 1V	DC12V± 1V
Power Consumption	3.6 W	5.7 W
Operating Temperature	0°C~50°C	0°C~50°C
Storage Temperature	-25°C~80°C	-25°C~80°C
Weight	190 g	367 g
Video Input	Composite NTSC 1.0Vp-p PAL 1.0Vp-p	Composite NTSC 1.0Vp-p PAL 1.0Vp-p
Brightness	270 cd/m ²	500 cd/m ²

●仕様は予告なく変更する場合がございます。詳細はお問い合わせ願います。
Specifications are subject to change with or without notice. Please contact us.

仕様 Specification

Model	YIP-A5604HB
Display Method	Color TFT LCD
Back Light	CCFL
Resolution	960 (H) x 234 (V) dot
Active Area (mm)	113.3 (H) x 84.7 (V)
Dot Pitch (mm)	0.118 (H) x 0.362 (V)
Pixel Configuration	R.G.B Stripe
View Angle	Top : 30° Bottom : 50° Right : 50° Left : 50°
Dimension (mm)	130.0 (W) x 103.7 (H) x 19.2 (D)
Input Voltage	DC12V± 1V
Power Consumption	4.5 W
Operating Temperature	0°C~50°C
Storage Temperature	-25°C~60°C
Weight	201 g
Video Input	Composite NTSC 1.0Vp-p PAL 1.0Vp-p
Brightness	500 cd/m ²

●仕様は予告なく変更する場合がございます。詳細はお問い合わせ願います。
Specifications are subject to change with or without notice. Please contact us.

仕様 Specification

Model	YIP-P6401	YIP-P6404
Display Method	Color TFT LCD	Color TFT LCD
Back Light	CCFL	CCFL
Resolution	960 (H) x 234 (V) dot	960 (H) x 234 (V) dot
Active Area (mm)	129.6 (H) x 97.34 (V)	129.6 (H) x 97.34 (V)
Dot Pitch (mm)	0.135 (H) x 0.416 (V)	0.135 (H) x 0.416 (V)
Pixel Configuration	R.G.B Stripe	R.G.B Stripe
View Angle	Top : 40° Bottom : 50° Right : 60° Left : 60°	Top : 40° Bottom : 40° Right : 55° Left : 55°
Dimension (mm)	156.3 (W) x 119.8 (H) x 19.9 (D)	148.88 (W) x 113.95 (H) x 7.2 (D)
Input Voltage	DC12V± 1V	DC12V± 1V
Power Consumption	5 W	6 W
Operating Temperature	0°C~50°C	0°C~50°C
Storage Temperature	-30°C~80°C	-30°C~80°C
Weight	300 g	223 g
Video Input	1) Composite NTSC 1.0Vp-p PAL 1.0Vp-p 2) Analog R/G/B Video Level : 0.7Vp-p Sync Level : 5.0Vp-p	1) Composite NTSC 1.0Vp-p PAL 1.0Vp-p
Brightness	330 cd/m ²	330 cd/m ²

●仕様は予告なく変更する場合がございます。詳細はお問い合わせ願います。
Specifications are subject to change with or without notice. Please contact us.

仕様 Specification

Model	YIP-A7001
Display Method	Color TFT LCD
Back Light	CCFL
Resolution	1440 (H) x 234 (V) dot
Active Area (mm)	154.08 (H) x 86.58 (V)
Dot Pitch (mm)	0.107 (H) x 0.370 (V)
Pixel Configuration	R.G.B Stripe
View Angle	Top : 30° Bottom : 60° Right : 60° Left : 60°
Dimension (mm)	183.6 (W) x 105.2 (H) x 26.0 (D)
Input Voltage	DC12V± 1V
Power Consumption	7.8 W
Operating Temperature	0°C~50°C
Storage Temperature	-25°C~80°C
Weight	300 g
Video Input	1) Composite NTSC 1.0Vp-p PAL 1.0Vp-p 2) Analog R/G/B Video Level : 0.7Vp-p Sync Level : 5.0Vp-p
Brightness	420 cd/m ²

●仕様は予告なく変更する場合がございます。詳細はお問い合わせ願います。
Specifications are subject to change with or without notice. Please contact us.